Safety Data Sheet

Printing date 08/28/2020 Revised On 08/28/2020

1 Identification of the substance and manufacturer

Trade name: **NEW ORANGE** Product code: BC08450000

Recommended use: Paint and coatings application.

Uses advised against: Any that differs from the recommended use.

Seymour of Sycamore Manufacturer/Supplier:

917 Crosby Avenue Sycamore, IL 60178 USA phone: 815-895-9101 www.seymourpaint.com

1-800-255-3924 **Emergency telephone number:**

Seymour of Sycamore 3041 Dougall Avenue, Suite 503 Windsor, ONT N9E 1S3 CANADA phone: 800-435-4482

www.seymourpaint.com

2 Hazard(s) identification

Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.

Press. Gas H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation. Eye Irrit. 2A

STOT SE 3 H336 May cause drowsiness or dizziness.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

GHS Hazard pictograms

Precautionary statements





GHS02 GHS04 GHS07 GHS08

Signal word Danger

Hazard statements Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes serious eye irritation. May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure. Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash hands thoroughly after handling.
Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection. IF INHALED: Remove person to fresh air and keep comfortable for breathing

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:				
67-64-1	Acetone	25-50%		
	propane	15-25%		
	Isobutyl Acetate	10-15%		
106-97-8		5-10%		
	PM acetate	1-5%		
	methyl isobutyl ketone	1-5%		
	Methyl Propyl Ketone	1-5%		
	titanium dioxide	1-5%		
2807-30-9	Glycol Ether EP	1-5%		

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

Remove contaminated clothing. Wash exposed area with soap and water. After skin contact:

After eve contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

Rinse mouth with water. Do not induce vomiting. After swallowing:

Most important symptoms and Dizziness effects:

(Contd. on page 2)

(Contd. of page 1)

Printing date 08/28/2020 Revised On 08/28/2020

Trade name: NEW ORANGE

Indication of any immediate medical attention needed:

No further relevant information available.

5 Fire-fighting measures

Extinguishing agents: Special hazards:

Protective equipment for

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

Can form explosive gas-air mixtures.

firefighters: A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective equipment and emergency

procedures:

Methods and material for containment and cleaning up: Use respiratory protective device against the effects of fumes/dust/aerosol.

Absorb liquid components with liquid-binding material.

7 Handling and storage

Precautions for safe handling

Storage requirements:

Use only in well ventilated areas.

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.

Store locked up.

8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:
67-64-1 Acetone

b	۱٠	-6	4-	1	F	10	ce	τ	n	е

PEL (USA) Long-term value: 2400 mg/m³, 1000 ppm REL (USA) Long-term value: 590 mg/m³, 250 ppm TLV (USA) Short-term value: 1187 mg/m³, 500 ppm

Long-term value: 594 mg/m³, 250 ppm

74-98-6 propane

PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm REL (USA) Long-term value: 1800 mg/m³, 1000 ppm TLV (USA) refer to Appendix F inTLVs&BEIs book; D, EX

110-19-0 Isobutyl Acetate

PEL (USA) Long-term value: 700 mg/m³, 150 ppm REL (USA) Long-term value: 700 mg/m³, 150 ppm Short-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm TLV (USA)

106-97-8 n-butane

REL (USA) Long-term value: 1900 mg/m³, 800 ppm TLV (USA) Short-term value: 2370 mg/m3, 1000 ppm (EX)

108-65-6 PM acetate

WEEL (USA) Long-term value: 50 ppm

108-10-1 methyl isobutyl ketone

PEL (USA) Long-term value: 410 mg/m³, 100 ppm REL (USA)

Short-term value: 300 mg/m³, 75 ppm

Long-term value: 205 mg/m³, 50 ppm

Short-term value: 307 mg/m³, 75 ppm TLV (USA) Long-term value: 82 mg/m³, 20 ppm

BEI

107-87-9 Methyl Propyl Ketone

PEL (USA) Long-term value: 700 mg/m³, 200 ppm REL (USA) Long-term value: 530 mg/m³, 150 ppm TLV (USA) Short-term value: 529 mg/m³, 150 ppm

Ingredients with biological limit values:

67-64-1 Acetone

BEI (USA) 50 mg/L

Medium: urine Time: end of shift

Parameter: Acetone (nonspecific)

(Contd. on page 3)

(Contd. of page 2)

Printing date 08/28/2020 Revised On 08/28/2020

Trade name: NEW ORANGE

108-10-1 methyl isobutyl ketone

BEI (USA) 1 mg/L

Medium: urine Time: end of shift Parameter: MIBK

Immediately remove all soiled and contaminated clothing. Hygienic protection:

Wash hands after use.

Avoid contact with the eyes and skin.

Do not eat or drink while working.

A respirator is generally not necessary when using this product outdoors or in large open areas. In **Breathing equipment:** cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn.

If you suspect overexposure conditions exist, please consult an authority on chemical hygeine.

Hand protection: Nitrile gloves.

The glove material must be impermeable and resistant to the substance.

Tightly sealed goggles Eye protection:

9 Physical and chemical properties

Appearance: Aerosol. Odor: Aromatic Not determined. Odor threshold: Not determined. pH-value: Melting point/Melting range Undetermined. **Boiling point:** -44.5 °C (-48.1 °F) -19 °C (-2.2 °F) Flash point: Flammability (solid, gas): Extremely flammable.

Not determined. Decomposition temperature:

Auto igniting: Product is not self-igniting.

In use, may form flammable/explosive vapour-air mixture. Danger of explosion:

1.7 Vol % Lower Explosion Limit: Upper Explosion Limit: 10.9 Vol % Vapor pressure: Not determined.

Relative Density: Between 0.77 and 0.85 (Water equals 1.00)

Vapor density Not determined. Evaporation rate Not applicable. Partition coefficient: n-octonal/water: Not determined. Not determined. Solubility: Viscosity: Not determined.

Water: 0.0 %

10 Stability and reactivity

Reactivity: Stable at normal temperatures.

Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing

temperatures.

Chemical stability: Not fully evaluated.

No dangerous reactions known. Possibility of hazardous reactions:

Incompatible materials: No further relevant information available. Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information

	•					
LD/LC50 values that are relevant for classification:						
110-19-0 I	110-19-0 Isobutyl Acetate					
Oral	Oral LD50 4,763 mg/kg (rbt)					
108-65-6 F	108-65-6 PM acetate					
Oral	LD50	8,500 mg/kg (rat)				
Inhalative	Inhalative LC50/4 h 35.7 mg/l (rat)					
108-10-1 r	108-10-1 methyl isobutyl ketone					
Oral	LD50	2,100 mg/kg (rat)				
Dermal	LD50	16,000 mg/kg (rab)				
Inhalative	Inhalative LC50/4 h 8.3-16.6 mg/l (rat)					
13463-67-	13463-67-7 titanium dioxide					
Oral	LD50	>20,000 mg/kg (rat)				
Dermal	LD50	>10,000 mg/kg (rbt)				
Inhalative	Inhalative LC50/4 h >6.82 mg/l (rat)					

Information on toxicological effects: No data available. No irritant effect. Skin effects:

(Contd. of page 3)

Safety Data Sheet

Printing date 08/28/2020 Revised On 08/28/2020

Trade name: NEW ORANGE

Eye effects: Irritating effect.

Sénsitization: No sensitizing effects known.

12 Ecological information

Aquatic toxicity:

Hazardous for water, do not empty into drains.

Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes. Other information:

This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated

solvents.

No further relevant information available. Bioaccumulative potential: No further relevant information available. Mobility in soil: Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Completely empty cans should be recycled. Recommendation:

14 Transport information

UN-Number UN1950 DOT N/A

Consumer Commodity ORM-D

Aerosols, flammable

ADR 1950 AEROSOLS

Transport hazard class(es):

Class

Warning: Gases Special precautions for user:

EMS Number: F-D,S-U

Packaging Group: UN "Model Regulation":

UN 1950 AEROSOLS, 2.1

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

108-10-1 methyl isobutyl ketone

Toxic Substances Control Act

(TSCA): All hazardous ingredients are found on the inventory list of substances.

Canadian Domestic Substances List

(DSL): All ingredients are listed or exempted.

Consumer Product Safety

Comission (CPSC): This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California F	roposition 65	cnemicais	known to	cause cancer:

108-10-1 methyl isobutyl ketone

13463-67-7 titanium dioxide

100-41-4 ethyl benzene

Prop 65 chemicals known to cause birth defects or reproductive harm:

108-10-1 methyl isobutyl ketone

EPA:

67-64-1	1 Acetone	
110-19-0	Isobutyl Acetate	D
108-10-1	methyl isobutyl ketone	Ι

16 Other information

Contact: Regulatory Affairs